# SAFETY DATA SHEET

North American Version

# HYDROGEN PEROXIDE (35% =< Conc. < 50%)

# **1. PRODUCT AND COMPANY IDENTIFICATION**

1.1. Identification of the substance or mixture		
Product name Product grade(s)	<ul> <li>HYDROGEN PEROXIDE (35% =&lt; Conc. &lt; 50%)</li> <li>Interox® PFP 35% Hydrogen Peroxide Interox® HP Food 35% Hydrogen Peroxide Interox® Chem Grade 35% Interox® Cosmetic Grade 35% Interox® Food Grade 35% Hydrogen Peroxide Interox® Universal Food Grade 35% Hydrogen Peroxide Interox® Standard 35% Hydrogen Peroxide Interox® Storage Grade 35% Hydrogen Peroxide Interox® Storage Grade 35% Hydrogen Peroxide Interox® Technical Grade 35% Hydrogen Peroxide Interox® Technical Grade 35/D Hydrogen Peroxide Interox® Technical Grade 40% Hydrogen Peroxide Interox® Crude Grade 40% Hydrogen Peroxide Interox® SG 35 Hydrogen Peroxide</li> <li>Interox® SG 35 Hydrogen Peroxide</li> <li>Interox® PH-35/3 Hydrogen Peroxide</li> <li>Hydrogen Peroxide</li> </ul>	
Chemical Name Synonyms	: Hydrogen peroxide : Hydrogenoxide Hydrogen dioxide Hydrogen peroxide agueous solution	
Molecular formula	: H2O2	
Molecular Weight	: 34 g/mol	
1.2. Use of the Substance/Mixture		
Recommended use	<ul> <li>Bleaching agent</li> <li>Chemical industry</li> <li>Electronic industry</li> <li>Metal treatment</li> <li>Odour agents</li> <li>Oxidising Agents</li> <li>Textile industry</li> <li>Water treatment</li> <li>Pulp and paper</li> </ul>	
Recommended use	- Food additive	
1.3. Company/Undertaking Identification	ation	
Address	: SOLVAY CHEMICALS, INC. 3333 RICHMOND AVENUE HOUSTON TX 77098-3099 United States	
1.4. Emergency and contact telepho	one numbers	
Emergency telephone number	<ul> <li>1 (800) 424-9300 CHEMTREC ® (USA &amp; Canada)</li> <li>01-800-00-214-00 (MEX. REPUBLIC)</li> </ul>	
Contact telephone number	: US: +1-800-765-8292 (Product information)	





(pr	oduct information):		US: +1-713-525-6500 (Product information)	
2. HAZ/	ARDS IDENTIFICAT	ION		
2.1. Eme NFF HMI	r <b>gency Overview:</b> PA S	:	H= 3 F= 0 I= 1 S= OX H= 3 F= 0 R= 1 PPE = Supplied by User; dependent on local conditions	
Gene	eral Information			
	Appearance	:	liquid	
	Colour	:	colourless	
	Odour	:	pungent	
Main -	effects none			
2.2. Pote	ntial Health Effects:			
Inha -	<b>lation</b> nhalation of vapours is ir	ritating	to the respiratory system, may cause throat pain and cough.	

- Risk of: Nose bleeding, chronic bronchitis.

### Eye contact

- Corrosive
- May cause irreversible eye damage.
- Symptoms: Redness, Lachrymation, Swelling of tissue.

# Skin contact

- Irritation
- Risk of: Burn.

# Ingestion

- Severe irritation
- Symptoms: Nausea, Abdominal pain, Vomiting, Diarrhoea, Risk of chemical pneumonitis from product inhalation..

# Other toxicity effects

- See section 11: Toxicological Information

### 2.3. Environmental Effects:

- See section 12: Ecological Information

# **3. COMPOSITION/INFORMATION ON INGREDIENTS**

Hydrogen peroxide		
CAS-No.	:	7722-84-1
Concentration	:	>= 35.0 - < 50.0 %

# **4. FIRST AID MEASURES**

### 4.1. Inhalation

- Move to fresh air.
- If symptoms persist, call a physician.

# 4.2. Eye contact

- Call a physician or poison control centre immediately.
- In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
- In the case of difficulty of opening the lids, administer an analgesic eye wash (oxybuprocaine).

### 4.3. Skin contact

- Remove and wash contaminated clothing before re-use.
- Wash off with soap and water.
- If symptoms persist, call a physician.

### 4.4. Ingestion

- Rinse mouth with water.
- Do NOT induce vomiting.
- If accidentally swallowed obtain immediate medical attention.
- Oxygen or artificial respiration if needed.

#### 4.5. Notes to physician

# Exposure to decomposition products :

- Consult with an ophthalmologist immediately in all cases.
- If accidentally swallowed obtain immediate medical attention.
- When symptoms persist or in all cases of doubt seek medical advice.

# **5. FIREFIGHTING MEASURES**

### 5.1. Suitable extinguishing media

- Water
- Water spray

### 5.2. Extinguishing media which shall not be used for safety reasons

None.

### 5.3. Special exposure hazards in a fire

- Oxygen released in thermal decomposition may support combustion
- Contact with combustible material may cause fire.
- Contact with flammables may cause fire or explosions.
- Risk of explosion if heated under confinement.

#### 5.4. Hazardous decomposition products

- Oxygen

### 5.5. Special protective equipment for firefighters

- In the event of fire, wear self-contained breathing apparatus.
- Use personal protective equipment.
- Wear chemical resistant oversuit
- Cool containers / tanks with water spray.
- Prevent fire extinguishing water from contaminating surface water or the ground water system.

# 6. ACCIDENTAL RELEASE MEASURES

### 6.1. Personal precautions, protective equipment and emergency procedures

#### 6.1.1. Advice for non-emergency personnel

- Prevent further leakage or spillage if safe to do so.
- Keep away from Incompatible products.

### 6.1.2. Advice for emergency responders

- Evacuate personnel to safe areas.
- Keep people away from and upwind of spill/leak.
- Use personal protective equipment.

### 6.2. Environmental precautions

- In case of accidental release or spill, immediately notify the appropriate authorities if required by Federal, State/Provincial and local laws and regulations.
- Do not dump into any sewers, on the ground, or into any body of water. All disposal methods must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations.

### 6.3. Methods and materials for containment and cleaning up

- Dam up.
- Do not mix waste streams during collection.
- Soak up with inert absorbent material.
- Keep in suitable, closed containers for disposal.
- Never return spills in original containers for re-use.

### 6.4. Reference to other sections

Refer to protective measures listed in sections 7 and 8.

# 7. HANDLING AND STORAGE

#### 7.1. Handling

- Use only in well-ventilated areas.
- Use only clean and dry utensils.
- Never return unused material to storage receptacle.
- Keep away from heat.
- Avoid inhalation, ingestion and contact with skin and eyes.
- Keep away from Incompatible products.

#### 7.2. Storage

- Keep only in the original container.
- Store in a receptacle equipped with a vent.
- Store in a well-ventilated place. Keep cool.
- Keep container closed.
- Keep in a bunded area.
- Keep away from Incompatible products.
- Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- Regularly check the condition and temperature of the containers.
- Electrical equipment should be protected to the appropriate standard.

### 7.3. Packaging material

- aluminium 99.5 %
- stainless steel 304L / 316L
- Approved grades of HDPE.

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Exposure Limit Values

#### Hydrogen peroxide

- US. ACGIH Threshold Limit Values 02 2012
- time weighted average = 1 ppm
- US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000) 02 2006

Permissible exposure limit = 1 ppm Permissible exposure limit = 1.4 mg/m3

- US. OSHA Table Z-1-A (29 CFR 1910.1000) 1989
- time weighted average = 1 ppm time weighted average = 1.4 mg/m3 US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A 06 2008
- <u>US. Tennessee. OELs. Occupational Exposure Limits, Table Z1A\_06 2008</u> time weighted average = 1 ppm time weighted average = 1.4 mg/m3

ACGIH® and TLV® are registered trademarks of the American Conference of Governmental Industrial Hygienists. SAEL = Solvay Acceptable Exposure Limit, Time Weighted Average for 8 hour workdays. No Specific TLV STEL (Short Term Exposure Level) has been set. Excursions in exposure level may exceed 3 times the TLV TWA for no more than a total of 30 minutes during a workday and under no circumstances should they exceed 5 times the TLV TWA.

# 8.2. Engineering controls

- Ensure adequate ventilation.
- Apply technical measures to comply with the occupational exposure limits.

# 8.3. Personal protective equipment

# 8.3.1. Respiratory protection

- Self-contained breathing apparatus in confined spaces/insufficient oxygen/in case of large uncontrolled emissions/in all circumstances when the mask and cartridge do not give adequate protection.
- Use only respiratory protection that conforms to international/ national standards.
- Use NIOSH approved respiratory protection.
- Wear an approved full-face air supplied respirator for excessive or unknown concentrations. Selected
  chemical cartridges for respirators, i.e. OV, OV/AG, GME have been tested successfully under lab conditions
  to remove hydrogen peroxide and peracetic acid vapors in concentrations exceeding the applicable exposure
  limits. Further information is available in a Solvay Chemicals, Inc. Technical Communication, located at
  http://www.solvaychemicals.us/resource.htm in the Peractic Acid section.

# 8.3.2. Hand protection

- Impervious gloves
- Suitable material: PVC, Natural Rubber, butyl-rubber, Nitrile rubber
- Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact).

### 8.3.3. Eye protection

- Chemical resistant goggles must be worn.
- If splashes are likely to occur, wear: Tightly fitting safety goggles, Face-shield

### 8.3.4. Skin and body protection

- Chemical resistant apron
- Suitable material
- PVC
- Natural Rubber
- If splashes are likely to occur, wear: Apron, Boots

### 8.3.5. Hygiene measures

- Eye wash bottles or eye wash stations in compliance with applicable standards.
- Take off contaminated clothing and shoes immediately.
- Wash contaminated clothing before re-use.
- When using do not eat, drink or smoke.
- Wash hands before breaks and at the end of workday.
- Handle in accordance with good industrial hygiene and safety practice.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1.	9.1. General Information		
	Appearance	:	liquid
	Colour	:	colourless
	Odour	:	pungent
9.2.	Important health safety and e	nvi	ronmental information
	pH pKa	:	2.02 (H2O2 50 %) pKa1= 11.62 <i>Temperature</i> : 25 °C ( 77 °F )
	Boiling point/boiling range	:	108 °C ( 226 °F ) (H2O2 35 %)
	Flash point	:	Remarks: not applicable
	Flammability	:	Remarks: The product is not flammable.
	Explosive properties	:	<u>Explosion danger</u> : <i>Remarks</i> : Not explosive
	Oxidizing properties	:	Remarks: Non oxidizer
	Vapour pressure	:	1 mbar (H2O2 50 %) <i>Temperature</i> : 30 °C ( 86 °F )
	Relative density / Density	:	1.1 - 1.2
	Bulk density	:	Remarks: not applicable
	Solubility(ies)	:	Remarks: no data available
	Partition coefficient: n-octanol/water	:	<u>log Pow</u> : -1.57 <i>Method</i> : calculated value
	Viscosity	:	1.17 mPa.s (H2O2 50 %) <i>Temperature</i> : 20 °C ( 68 °F )
	Vapour density	:	1
9.3.	Other data		
	Freezing point:	:	-33 °C (-27 °F)(H2O2 35 %)
	Auto-flammability	:	Remarks: The product is not flammable.
	Surface tension	:	75.6 mN/m (H2O2 50 %) <i>Temperature</i> : 20 °C(68 °F)
	Decomposition temperature	:	>= 60 °C ( 140 °F ) <i>Remarks</i> : Self-Accelerating decomposition temperature (SADT) < 60 °C ( 140 °F ) <i>Remarks</i> : Slow decomposition

# **10. STABILITY AND REACTIVITY**

# 10.1. Stability

- Stable under recommended storage conditions.

### 10.2. Conditions to avoid

- Contamination
- To avoid thermal decomposition, do not overheat.
- Keep at temperature not exceeding: 60 °C (140 °F)
- Keep at temperature not exceeding: 60 °C (140 °F)

### 10.3. Materials to avoid

 Acids, Bases, Metals, Heavy metal salts, Powdered metal salts, Reducing agents, Organic materials, Flammable materials

# 10.4. Hazardous decomposition products

Oxygen

# **11. TOXICOLOGICAL INFORMATION**

# **Toxicological data**

# Acute oral toxicity

LD50, rat, 1,193 - 1,270 mg/kg (H2O2 35 %)

### Acute inhalation toxicity

LC50, 4 h, rat, > 0.17 mg/l, Remarks: vapour (H2O2 50 %)

# Acute dermal irritation/corrosion

LD50, rabbit, > 2,000 mg/kg (H2O2 35 %)

### Skin irritation

- rabbit, Skin irritation (H2O2 35 %)

### Eye irritation

rabbit, Severe eye irritation (H2O2 10%)

### Sensitisation

- guinea pig, Did not cause sensitization on laboratory animals.

### Chronic toxicity

- Oral, 90-day, mouse, Target Organs: Gastrointestinal tract, Lowest observable effect level: 300 ppm, LOAEL
- Oral, 90-day, mouse, NOEL: 100 ppm, NOAEL
- Inhalation, 28-day, rat, Target Organs: Respiratory system, Lowest observable effect level: 10 ppm, LOAEL, vapour
- Inhalation, 28-day, rat, NOEL: 2 ppm, NOAEL, vapour

### Carcinogenicity

- Oral, Prolonged exposure, mouse, Target Organs: duodenum, carcinogenic effects
- Dermal, Prolonged exposure, mouse, Animal testing did not show any carcinogenic effects.

### Genetic toxicity in vitro

- In vitro tests have shown mutagenic effects.

### Genetic toxicity in vivo

In vivo tests did not show mutagenic effects

### Reproductive toxicity

- Substance is totally biotransformed (metabolised).
- study scientifically unjustified

### Remarks

- no data available

# **12. ECOLOGICAL INFORMATION**

# 12.1. Ecotoxicity effects

### Acute toxicity

- Fishes, Pimephales promelas, LC50, 96 h, 16.4 mg/l
- Fishes, Pimephales promelas, NOEC, 96 h, 4.3 mg/l
- Crustaceans, Daphnia pulex, EC50, 48 h, 2.4 mg/l Remarks: fresh water, semi-static test
- Crustaceans, Daphnia pulex, NOEC, 48 h, 1 mg/l Remarks: fresh water, semi-static test

### Chronic toxicity

- Algae, Skeletonema costatum, EC50, growth rate, 72 h, 2.6 mg/l
- Algae, Skeletonema costatum, NOEC, 72 h, 0.63 mg/l
- Algae, Chlorella vulgaris, EC50, Growth rate, 72 h, 4.3 mg/l
- Algae, Chlorella vulgaris, NOEC, 72 h, 0.1 mg/l

# 12.2. Mobility

- <u>Air</u>, Volatility, Henry's law constant (H) = 0.75 kPa.m<sup>3</sup>/mol Conditions: 20 °C Remarks: not significant
  - Water
  - Remarks: considerable solubility and mobility
- <u>Soil/sediments</u>, log KOC:0.2 Remarks: non-significant evaporation and adsorption

# 12.3. Persistence and degradability

### Abiotic degradation

- Air, indirect photo-oxidation, t 1/2 24 h Conditions: sensitizer: OH radicals
- <u>Water</u>, redox reaction, t 1/2 120 h Conditions: mineral and enzymatic catalysis, fresh water, salt water
- <u>Soil</u>, redox reaction, t 1/2 12 h Conditions: mineral and enzymatic catalysis

### Biodegradation

- aerobic, t 1/2 < 2 min</li>
   Conditions: biological treatment sludge
   Remarks: Readily biodegradable.
- aerobic, t 1/2 from 0.3 5 d
   Conditions: fresh water
   Remarks: Readily biodegradable.
- anaerobic
   Conditions: Soil/sediments
   Remarks: not applicable

# 12.4. Bioaccumulative potential

- Bioaccumulative potential: -1.57 Result: Does not bioaccumulate.

# 12.5. Other adverse effects

- no data available
- 12.6. Remarks

# **13. DISPOSAL CONSIDERATIONS**

# 13.1. Waste from residues / unused products

- Limited quantity -
- Dilute with plenty of water. -
- Flush into sewer with plenty of water. -
- Maximum quantity -
- Contact manufacturer. -
- Contact waste disposal services. -
- In accordance with local and national regulations.

# 13.2. Packaging treatment

- Empty containers.
- Clean container with water.
- Dispose of rinse water in accordance with local and national regulations.
- Where possible recycling is preferred to disposal or incineration. -
- In accordance with local and national regulations. \_

# 13.3. RCRA Hazardous Waste

- Listed RCRA Hazardous Waste (40 CFR 302) No
- Unlisted RCRA Hazardous Waste (40 CFR 302) Yes -
- D001 (ignitable waste) -
- D002 (corrosive waste) -

# **14. TRANSPORT INFORMATION**

# **IATA-DGR**

	UN number	UN 2014
	Class	5.1
	Packing group	II
	ICAO-Labels	5.1 - Oxidizing substances 8 - Corrosive
	Proper shipping name: HYDROGEN PERO	XIDE, AQUEOUS SOLUTION
IMDG		
	UN number	UN 2014
	Class	5.1
	Packing group	II
	IMDG-Labels	5.1 - Oxidizing substances 8 - Corrosive
	EmS	F-H
		S-Q
	Proper shipping name: HYDROGEN PERO	XIDE, AQUEOUS SOLUTION
U.S. De	ept of Transportation	
	UN number	UN 2014
	Class	5.1

Class	5.1
Packing group	II
Label	5.1 - Oxidizing substances 8 - Corrosive
EmS	140
Remarks	UN 1066, NITROGEN COMPRESSED, 2.2

Proper shipping name: HYDROGEN PEROXIDE, AQUEOUS SOLUTION

Canada	a (TDG)	
	UN number	UN 2014
	Class	5.1
	Packing group	II
	Label	5.1 - Oxidizing substances 8 - Corrosive
	EmS	140
	Proper shipping name: HYDROGEN PERO	XIDE, AQUEOUS SOLUTION
Mexico	• (NOM-002-SCT)	
	UN number	UN 2014

UN number	UN 2014
Class	5.1
Packing group	II
Label	5.1 - Oxidizing substances 8 - Corrosive

- IATA: forbidden over 40 %

# **15. REGULATORY INFORMATION**

# 15.1. Inventory Information

Toxic Substance Control Act list (TSCA)	: - In compliance with inventory.
Australian Inventory of Chemical	: - In compliance with inventory.
Substances (AICS)	
Canadian Domestic Substances	: - In compliance with inventory.
Korean Existing Chemicals	: - In compliance with inventory.
Inventory (KECI (KR))	
EU list of existing chemical	: - In compliance with inventory.
substances (EINECS)	
Japanese Existing and New	: - In compliance with inventory.
Chemical Substances (MITI List)	
(ENCS)	
Inventory of Existing Chemical	: - In compliance with inventory.
Substances (China) (IECS)	
Philippine Inventory of Chemicals	: - In compliance with inventory.
and Chemical Substances	
(PICCS)	
New Zealand Inventory of	: - In compliance with inventory.
Chemicals (NZIOC)	

# 15.2. Other regulations

# US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A)

- not regulated.

### SARA Hazard Designation (SARA 311/312)

Acute Health Hazard: Yes.

- Fire Hazard: Yes.

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 313 Toxic Chemicals (40 CFR 372.65) - Supplier Notification Required

- not regulated.
- US. EPA CERCLA Hazardous Substances (40 CFR 302)
  - not regulated.
- US. New Jersey Worker and Community Right-to-Know Act (New Jersey Statute Annotated Section 34:5A-5) - yes.
- US. Pennsylvania Worker and Community Right-to-Know Law (34 Pa. Code Chap. 301-323)

· yes.

- US. California Safe Drinking Water & Toxic Enforcement Act (Proposition 65)
  - not regulated.

# **16. OTHER INFORMATION**

### Ratings :

# NFPA (National Fire Protection Association)

Health = 3 Flammability = 0 Instability = 1 Special =OX

# HMIS (Hazardous Material Information System)

Health = 3 Fire = 0 Reactivity = 1 PPE : Supplied by User; dependent on local conditions

# **Further information**

- New (SDS)
- Distribute new edition to clients
- The National Transportation Safety Board (NTSB) and Federal Aviation Administration (FAA) have requested the following information be provided:
- Combustible materials exposed to hydrogen peroxide should be immediately submerged in or rinsed with large amounts of water to ensure that all hydrogen peroxide is removed.
- Residual hydrogen peroxide that is allowed to dry (upon evaporation hydrogen peroxide can concentrate) on organic materials such as paper, fabrics, cotton, leather, wood or other combustibles can cause the material to ignite and result in a fire.
- Wear an approved full-face air supplied respirator for excessive or unknown concentrations. Selected chemical cartridges for respirators, i.e. OV, OV/AG, GME have been tested successfully under lab conditions to remove hydrogen peroxide and peracetic acid vapors in concentrations exceeding the applicable exposure limits. Further information is available in a Solvay Chemicals, Inc. Technical Communication, located at http://www.solvaychemicals.us/resource.htm in the Peractic Acid section.

Material Safety Data Sheets contain country specific regulatory information; therefore, the MSDS's provided are for use only by customers of the company mentioned in section 1 in North America. If you are located in a country other than Canada, Mexico or the United States, please contact the Solvay Group company in your country for MSDS information applicable to your location.

The previous information is based upon our current knowledge and experience of our product and is not exhaustive. It applies to the product as defined by the specifications. In case of combinations or mixtures, one must confirm that no new hazards are likely to exist. In any case, the user is not exempt from observing all legal, administrative and

regulatory procedures relating to the product, personal hygiene, and integrity of the work environment. (Unless noted to the contrary, the technical information applies only to pure product).

To our actual knowledge, the information contained herein is accurate as of the date of this document. However, neither the company mentioned in section 1 nor any of its affiliates makes any warranty, express or implied, including merchantability or fitness for use, or accepts any liability in connection with this information or its use. This information is for use by technically skilled persons at their own discretion and risk and does not relate to the use of this product in combination with any other substance or any other process. This is not a license under any patent or other proprietary right. The user alone must finally determine suitability of any information or material for any contemplated use in compliance with applicable law, the manner of use and whether any patents are infringed. This information gives typical properties only and is not to be used for specification purposes. The company mentioned in section 1 reserves the right to make additions, deletions or modifications to the information at any time without prior notification.

Trademarks and/or other products of the company mentioned in section 1 referenced herein are either trademarks or registered trademarks of the company mentioned in section 1 or its affiliates, unless otherwise indicated.

Copyright 2011, Company mentioned in Section 1. All Rights Reserved.